

Eco-Friendly & Professional THE NEW LED LIGHT DISPLAY 32WL30



ECO-FRIENDLY

- Low Power Consumption
- Environmental Regulation : EPA, ERP
- No Harmful Material : RoHS, CO₂ Reduction

EASY INSTALLATION/ MAINTENANCE


- Slim and Light feature offers space saving and easy installation
- Easy to maintain remotely

IMPROVED BEZEL & DEPTH



WIDE VIEWING ANGLE

Providing clear image virtually at any angle.



THE NEW LED LIGHT DISPLAY

32WL30 32F"



FEATURES

- Eco-Friendly (EPA, ErP, RoHS, CO₂ Reduction)
- Low Power Consumption
- Slim Depth : 35.6mm
- Easy Installation & Maintenance
- Brightness : 400nit
- Wide Viewing Angle
- Media Player Integrated Solution (SuperSign Elite-w, Elite-w lite)

SPECIFICATIONS

32WL30

PANEL	Screen Size	32" (31.50" measured diagonal)
	Panel Technology	IPS (LED BLU)
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	400nit
	Contrast Ratio	1,300 : 1
	Dynamic CR	500,000 : 1
	Viewing Angle (H x V)	178 x 178
	Response Time	16ms (G to G, *WOT)
	CONNECTIVITY	Input (Rear)
Digital		HDMI(1), DVI-D(1) with HDCP for all input
Analog		RGB(1), Shared Component(1), AV(1)
Audio		RGB / DVI-D (3.5φ 1)
External Control		RS232C(1), RJ45(1)
USB		USB(1)
Output (Rear)		
Digital		No
Analog		No
Audio		External Speaker(1)
External Control		No
Audio		
Auto Volume		No
Balance		Yes
Audio Power		20W (10W x 2)
Speaker On/off	Yes	
Clear Voice II	Yes	
Sound mode	Standard, Music, Cinema, Sports, Game	

PHYSICAL SPECIFICATION	Bezel Width	18.9mm (Top / Left / Right), 26mm (Bottom)
	Monitor Dimension (W x H x D)	74.04cm x 44.2cm x 3.56cm
	Weight (head)	7.9kg
	Carton Dimensions (W x H x D)	80.5cm x 11.5cm x 59.0cm
	Packed Weight	9.8kg
SPECIAL FEATURES	VESA™ Standard Mount Interface	200mm x 200mm
	Additional	Smart Energy Saving, Multi-media playback, PIP/ PBP, Temp Sensor, Tile mode (Up to 5x5), ISM Method, Key Lock
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy Saving	65W(Typ) / 45W(SES)
	DPMS	1.0W (Set Only)
STANDARD(CERTIFICATION)	Power Off	0.5W
	Safety	UL / cUL / CB schem / TUV
MEDIA PLAYER COMPATIBILITY	EMC	FCC Class "B" / VCCI / C-tick / CE / KCC
	ErP / Energy Star	Yes / Yes (Energy Star 5.1)
	Slot PC compatible (optional)	No
SOFTWARE COMPATIBILITY	External Media player Attachable	Yes
	Supersign Compatibility	Elite-w / Elite-w lite
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG
	Optional	LSW200AX (Wall Mount), SP-2000 (Speaker), TBD (Stand)

* WOT : Within Operation Temperature
 ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

