

## SHINE-OUT DISPLAY 42VX30MS / 47VX30AS

- Perfect fit for window display
- Reflects away the sunlight for best image visibility
- Clearer display under direct sunlight than conventional panel
- Screen Size : 42", 47"
- Aspect Ratio : 16 : 9
- Native Resolution : 1920 x 1080 (FHD)
- Brightness : 700cd/m<sup>2</sup>
- Contrast Ratio : 1,200:1
- Viewing Angle (H x V) : 178 x 178
- Response Time : 10 ms (G to G)
- Audio Power : 20W (10W x 2)
- Speaker On/off : Yes
- Clear Voice : Yes
- Sound mode : Standard/Music/Cinema/Sports/Game/User
- Bezel width 16,9mm (42") / 17,9mm (47")




### KEY FEATURES



### SHINE OUT


Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.



Shine-Out (Outdoor Exclusive Panel)

### VIDEO WALL

Good for constructing video wall with narrow bezel size. It maximizes display effect through various size video wall.




5 x 5 MATRIX

### NO BLACKENING DEFECT

Even under direct sunlight exposure, LG commercial monitors that adopted LGD panel remain free of blackening defects and provides superior quality for semi-outdoor usage.



Super-IPS Panel



Conventional Panel


**42VX30MS**

**47VX30AS**

## SPECIFICATION

|                            |                                  | 42" Class (42.02" measured diagonal)                     | 47" Class (46.96" measured diagonal)   |
|----------------------------|----------------------------------|--|--|
| PANEL                      | Screen Size                      | 42" Class (42.02" measured diagonal)                     | 47" Class (46.96" measured diagonal)   |
|                            | Panel Technology                 | IPS  |  |
|                            | Aspect Ratio                     | 16:9   |  |
|                            | Native Resolution                | 1920x1080(FHD)   |  |
|                            | Brightness                       | 700cd/m <sup>2</sup>                                     |  |
|                            | Contrast Ratio                   | 1,200:1  |  |
|                            | Dynamic CR                       | 3,000:1  |  |
|                            | Viewing Angle(H x V)             | 178 x 178  |  |
|                            | Response Time                    | 9 ms(G to G)   |  |
| CONNECTIVITY               | Input (Rear)                     |  |  |
|                            | Digital                          | HDMI(1), DVI(1), Display Port(1) with HDCP for all input |  |
|                            | Analog                           | Component(1), AV(1), RGB(1) (Shared with D-Sub)          |  |
|                            | Audio                            | PC/AV/Component Audio In(1)                              |  |
|                            | External Control                 | RS232C(1), RJ45(1)                                       |  |
|                            | USB                              | USB(1)   |  |
|                            | Output (Rear)                    |  |  |
|                            | Digital                          | DVI-D(1)   |  |
|                            | Analog                           | Component(1), Composite(1), RGB(1) (Shared with D-Sub)   |  |
|                            | Audio                            | External speaker   |  |
| External Control           | RS232C                           |  |  |
| PHYSICAL SPECIFICATION     | Bezel Width                      | 16.9 mm  | 17.9mm                                 |
|                            | Monitor Dimension (W x H x D)    | 96.7cm X 56.1cm X 12.5cm                                 | 107.95cm x 62.46cm x 12.29cm           |
|                            | Weight (head)                    | 17.5kg   | 22.2kg                                 |
|                            | Carton Dimensions (W x H x D)    | 104.5cm x 66.0cm x 25.0cm                                | 118.2cm x 74.3cm x 26.9cm              |
|                            | Packed Weight                    | 21.87kg  | 29.6kg                                 |
|                            | VESA™ Standard Mount Interface   | 600 x 400  | 800 x 400                              |
| SPECIAL FEATURES           | Additional                       | Shine Out  |  |
| ENVIRONMENT CONDITIONS     | Operation Temperature            | 0 °C to 40 °C  |  |
|                            | Operation Humidity               | 10 % to 80 %   |  |
| POWER                      | Power Supply                     | 100-240V~, 50/60Hz                                       |  |
|                            | Power Consumption                |  |  |
|                            | Typical / Smart Energy Saving on | 170W(typ)/130W(Smart Energy Saving on)                   | 180W(typ)/130W(Smart Energy Saving on) |
|                            | DPMS                             | 1.0W(Set only)   |  |
|                            | Power Off                        | 0.5W   |  |
| STANDARD (CERTIFICATION)   | Safety                           | UL / cUL / CB scheme / TUV                               |  |
|                            | EMC                              | FCC Class "B" / CE / KCC                                 |  |
|                            | ErP / Energy Star                | Yes / Yes (EPA 5.1)                                      |  |
| MEDIA PLAYER COMPATIBILITY | Slot PC compatible (optional)    | No   |  |
|                            | External Media player Attachable | Yes  |  |
| SOFTWARE COMPATIBILITY     | Supersign Compatibility          | Yes  |  |
| ACCESSORY                  | Included                         | Remote Controller, Power Cable, RGB Cable, Manual        |  |
|                            | Optional                         | AP-WX60 ST1000K (Stand), SP0000K (Speaker)               |  |

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.