

SHINE-OUT DISPLAY 42VX30MS / 47VX30AS

- Perfect fit for window display
- Reflects away the sunlight for best image visibility
- Clearer display under direct sunlight than conventional panel
- Screen Size : 42", 47"
- Aspect Ratio : 16 : 9
- Native Resolution : 1920 x 1080 (FHD)
- Brightness : 700cd/m²
- Contrast Ratio : 1,200:1
- Viewing Angle (H x V) : 178 x 178
- Response Time : 10 ms (G to G)
- Audio Power : 20W (10W x 2)
- Speaker On/off : Yes
- Clear Voice : Yes
- Sound mode : Standard/Music/Cinema/Sports/Game/User
- Bezel width 16,9mm (42") / 17,9mm (47")




KEY FEATURES



SHINE OUT


Perfect fit for window display by reflecting away the sunlight for best image visibility and clearer display under direct sunlight than conventional panel.



Shine-Out (Outdoor Exclusive Panel)

VIDEO WALL

Good for constructing video wall with narrow bezel size. It maximizes display effect through various size video wall.




5 x 5 MATRIX

NO BLACKENING DEFECT

Even under direct sunlight exposure, LG commercial monitors that adopted LGD panel remain free of blackening defects and provides superior quality for semi-outdoor usage.



Super-IPS Panel



Conventional Panel


42VX30MS

47VX30AS

SPECIFICATION

		42" Class (42.02" measured diagonal)	47" Class (46.96" measured diagonal)
PANEL	Screen Size	42" Class (42.02" measured diagonal)	47" Class (46.96" measured diagonal)
	Panel Technology	IPS	
	Aspect Ratio	16:9	
	Native Resolution	1920x1080(FHD)	
	Brightness	700cd/m ²	
	Contrast Ratio	1,200:1	
	Dynamic CR	3,000:1	
	Viewing Angle(H x V)	178 x 178	
	Response Time	9 ms(G to G)	
CONNECTIVITY	Input (Rear)		
	Digital	HDMI(1), DVI(1), Display Port(1) with HDCP for all input	
	Analog	Component(1), AV(1), RGB(1) (Shared with D-Sub)	
	Audio	PC/AV/Component Audio In(1)	
	External Control	RS232C(1), RJ45(1)	
	USB	USB(1)	
	Output (Rear)		
	Digital	DVI-D(1)	
	Analog	Component(1), Composite(1), RGB(1) (Shared with D-Sub)	
	Audio	External speaker	
External Control	RS232C		
PHYSICAL SPECIFICATION	Bezel Width	16.9 mm	17.9mm
	Monitor Dimension (W x H x D)	96.7cm X 56.1cm X 12.5cm	107.95cm x 62.46cm x 12.29cm
	Weight (head)	17.5kg	22.2kg
	Carton Dimensions (W x H x D)	104.5cm x 66.0cm x 25.0cm	118.2cm x 74.3cm x 26.9cm
	Packed Weight	21.87kg	29.6kg
	VESA™ Standard Mount Interface	600 x 400	800 x 400
SPECIAL FEATURES	Additional	Shine Out	
ENVIRONMENT CONDITIONS	Operation Temperature	0 °C to 40 °C	
	Operation Humidity	10 % to 80 %	
POWER	Power Supply	100-240V~, 50/60Hz	
	Power Consumption		
	Typical / Smart Energy Saving on	170W(typ)/130W(Smart Energy Saving on)	180W(typ)/130W(Smart Energy Saving on)
	DPMS	1.0W(Set only)	
	Power Off	0.5W	
STANDARD (CERTIFICATION)	Safety	UL / cUL / CB scheme / TUV	
	EMC	FCC Class "B" / CE / KCC	
	ErP / Energy Star	Yes / Yes (EPA 5.1)	
MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	No	
	External Media player Attachable	Yes	
SOFTWARE COMPATIBILITY	Supersign Compatibility	Yes	
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual	
	Optional	AP-WX60 ST1000K (Stand), SP0000K (Speaker)	

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.