

# 5 Point Multi Touch & IR Spread INTERACTIVE WIDESPREAD TOUCH DISPLAY VT30

VT30 47"



## MULTI TOUCH

- IR Spread Type (1mm Touch Resolution)
- 5 Point Multi Touch (Windows 7)
- Ghost Free

\*IR Spread : LGE's own Cutting-edge Technology

## RELIABILITY

- Protection Glass (2.8mm)
- Anti Fog Film

## EASY INSTALLATION & MAINTENANCE

<p>Conventional</p> <p>*SIM</p>	<p>VT30</p> <p>*SIM : Slide in-Module</p>
<p>Time &amp; labor Required for Cabling</p>	<p>Simple Connection</p>

## SPACE SAVING

- PC Built-in Ready  
(Media Player - CPU : P4500, Core i5)

<p>External Media Player</p>	<p>Slot type Media Player</p>
----------------------------------	-----------------------------------

INTERACTIVE WIDESPREAD TOUCH DISPLAY

VT30 47F"



FEATURES

- LCD (PD Panel)
- 5 Point Multi Touch (Windows 7)
- IR Spread Type (1mm Touch Resolution)\*
- Slim Design for Space Saving
- PC Built-in Ready (Slot Type Media Player)
- High Reliability : Protection Glass & Anti Fog Film
- Easy Installation & Maintenance

\*IR Spread : LGE's own Cutting-edge Technology

SPECIFICATIONS

		VT30					
PANEL	Screen Size	47"		PHYSICAL SPECIFICATION	Bezel Width	34.2mm (Top / Bottom), 34.7mm (Left / Right)	
	Panel Technology	IPS			Monitor Dimension (W x H x D)	111.65cm x 66.05cm x 12.37cm	
	Aspect Ratio	16 : 9			Weight (head)	38.14kg	
	Native Resolution	1,920 x 1,080 (FHD)			Carton Dimensions (W x H x D)	140.6cm x 81.0cm x 30.0cm	
	Brightness	500nit			Packed Weight	42.46kg	
	Contrast Ratio	1,300 : 1			VESA™ Standard Mount Interface	800mm x 400mm	
	Dynamic CR	20,000 : 1			SPECIAL FEATURES	Additional	
	Viewing Angle (H x V)	178 x 178			ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Response Time	8ms (G to G, *WOT)			Operation Humidity	10% ~ 80%	
	CONNECTIVITY	Input (Rear)			POWER	Power Supply	100-240V~, 50/60Hz
Digital		HDMI / DVI(1) with HDCP		Power Consumption			
Analog		RGB / DVI(3.5Φ 1), Component(RCA 1), Composite(RCA 1)		Typical / Smart Energy Saving		250W	
Audio		RGB / DVI Audio, Component(RCA 1), Composite(RCA 1)		DPMS	1.0W (RGB), 1.0W (HDMI / DVI)		
External Control		RS232C(1), RJ45(1)		Power Off	0.5W		
USB		USB(1)		STANDARD(CERTIFICATION)	Safety	UL / c-UL / CB / Scheme / TUV	
Output (Rear)				EMC	FCC Class "A" / CE / KCC		
Digital		No		ErP / Energy Star	Yes / No		
Analog		RGB(1), Composite(BNC 1)		MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	Yes	
Audio		Composite(RAC 1), External Speaker		External Media player Attachable	Yes		
External Control		RS232C(1)		SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-s, eZ-net Manager	
Audio				ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG, USB Cable	
Auto Volume		Yes			Optional	No	
Balance		Yes					
Audio Power		20W (10W x 2)					
Speaker On/off		Yes					
Clear Voice II		Yes					
Sound mode	Standard, Music, Cinema, Sports, Game						

\* WOT : Within Operation Temperature  
 ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

