

5 Point Multi Touch & IR Spread INTERACTIVE WIDESPREAD TOUCH DISPLAY VT30

VT30 47"



MULTI TOUCH



- IR Spread Type (1mm Touch Resolution)
- 5 Point Multi Touch (Windows 7)
- Ghost Free

*IR Spread : LGE's own Cutting-edge Technology

RELIABILITY



- Protection Glass (2.8mm)
- Anti Fog Film

EASY INSTALLATION & MAINTENANCE

<p>Conventional</p>  <p>*SIM</p>	<p>VT30</p>  <p>*SIM : Slide in-Module</p>
<p>Time & labor Required for Cabling</p>	<p>Simple Connection</p>

SPACE SAVING

- PC Built-in Ready
(Media Player - CPU : P4500, Core i5)

 <p>External Media Player</p>	 <p>Slot type Media Player</p>
--	---

INTERACTIVE WIDESPREAD TOUCH DISPLAY

VT30 47F"



FEATURES

- LCD (PD Panel)
- 5 Point Multi Touch (Windows 7)
- IR Spread Type (1mm Touch Resolution)*
- Slim Design for Space Saving
- PC Built-in Ready (Slot Type Media Player)
- High Reliability : Protection Glass & Anti Fog Film
- Easy Installation & Maintenance

*IR Spread : LGE's own Cutting-edge Technology

SPECIFICATIONS

		VT30						
PANEL	Screen Size	47"		PHYSICAL SPECIFICATION	Bezel Width	34.2mm (Top / Bottom), 34.7mm (Left / Right)		
	Panel Technology	IPS			Monitor Dimension (W x H x D)	111.65cm x 66.05cm x 12.37cm		
	Aspect Ratio	16 : 9			Weight (head)	38.14kg		
	Native Resolution	1,920 x 1,080 (FHD)			Carton Dimensions (W x H x D)	140.6cm x 81.0cm x 30.0cm		
	Brightness	500nit			Packed Weight	42.46kg		
	Contrast Ratio	1,300 : 1			VESA™ Standard Mount Interface	800mm x 400mm		
	Dynamic CR	20,000 : 1			SPECIAL FEATURES	Additional		
	Viewing Angle (H x V)	178 x 178			ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C	
	Response Time	8ms (G to G, *WOT)			Operation Humidity	10% ~ 80%		
	CONNECTIVITY	Input (Rear)			POWER	Power Supply	100-240V~, 50/60Hz	
Digital		HDMI / DVI(1) with HDCP		Power Consumption				
Analog		RGB / DVI(3.5Φ 1), Component(RCA 1), Composite(RCA 1)		Typical / Smart Energy Saving		250W		
Audio		RGB / DVI Audio, Component(RCA 1), Composite(RCA 1)		DPMS	1.0W (RGB), 1.0W (HDMI / DVI)			
External Control		RS232C(1), RJ45(1)		Power Off	0.5W			
USB		USB(1)		STANDARD(CERTIFICATION)	Safety	UL / c-UL / CB / Scheme / TUV		
Output (Rear)				EMC	FCC Class "A" / CE / KCC			
Digital		No		ErP / Energy Star	Yes / No			
Analog		RGB(1), Composite(BNC 1)		MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	Yes		
Audio		Composite(RAC 1), External Speaker		External Media player Attachable	Yes			
External Control		RS232C(1)		SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-s, eZ-net Manager		
Audio				ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG, USB Cable		
Auto Volume		Yes			Optional	No		
Balance		Yes						
Audio Power		20W (10W x 2)						
Speaker On/off		Yes						
Clear Voice II		Yes						
Sound mode		Standard, Music, Cinema, Sports, Game						

* WOT : Within Operation Temperature
 ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

