

Eco-Friendly & Professional LED WIDESCREEN ULTRA HD DISPLAY 84WS70



84" EDGE LED LARGE SCREEN

Providing immersive wide viewing with high quality.



SUPER HIGH RESOLUTION 3,840 x 2,160 (ULTRA HD)



84WS70

HYBRID TYPE MEDIA PLAYER BUILT-IN READY

Making your signage look even slimmer and helps you maintain the system far more conveniently.



Slot type Media Player



MP700, MP500

MEDIA PLAYER INTEGRATED SOLUTION

The solution integrated with media player foregoes the need for additional media players and allows you to cut down expenses.



WS70 Series



USB Memory
(USB Multi-media
Playback)

+



Free Software
(SuperSign Elite-w lite)

LED WIDESCREEN ULTRA HD DISPLAY

84WS70 84U"



FEATURES

- 84" Edge LED Large Screen
- Super High Resolution : 3,840 x 2,160 (Ultra HD)
- Clear & Vivid Picture (Dynamic CR : 500,000 : 1) (TBD)
- Auto Brightness Sensor
- Smart Energy Saving
- Hybrid Type Media Player Built-in Ready (MP700, MP500)
- Media Player Integrated Solution (SuperSign Elite-w lite)

SPECIFICATIONS

84WS70

PANEL	Screen Size	84U"
	Panel Technology	IPS (LED BLU)
	Aspect Ratio	16 : 9
	Native Resolution	3,840 x 2,160 (Ultra HD)
	Brightness	500nit
	Contrast Ratio	1,400 : 1 (TBD)
	Dynamic CR	500,000 : 1 (TBD)
	Viewing Angle (H x V)	178 x 178
	Response Time	12ms (TBD)
	CONNECTIVITY	Input (Rear)
Digital		HDMI(2), DVI(1), Display Port(1)
Analog		Composit(1), RGB(1)
Audio		RGB / DVI-D / AV / Component (3.5Φ 1)
External Control		RS232C(1), RJ45(1), IR(1)
USB		USB(2)
Output (Rear)		
Digital		DVI-D(1)
Analog		Component(1), Composite(1), RGB(1) (Shared with D-Sub)
Audio		External Speaker(1)
External Control		RS232C(1), IR(1)
Audio		
Auto Volume		No
Balance		Yes
Audio Power		20W (10W x 2)
Speaker On/off	Yes	
Clear Voice II	Yes	
Sound mode	Standard, Music, Cinema, Sports, Game	

PHYSICAL SPECIFICATION	Bezel Width	27.9mm
	Monitor Dimension (W x H x D)	192.34cm x 110.94cm x 10.1cm (5.1cm)
	Weight (head)	TBD
	Carton Dimensions (W x H x D)	TBD
	Packed Weight	TBD
	VESA™ Standard Mount Interface	600mm x 400mm
SPECIAL FEATURES	Additional	Smart Energy Saving, Temp Sensor, Auto Brightness Sensor, ISM Method, Key Lock
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy Saving	350W(Typ) / 200W(SES)
	DPMS	1W (Set Only), 2W (With External Device)
	Power Off	0.5W
STANDARD(CERTIFICATION)	Safety	UL, cUL, CB scheme, TUV (TBD)
	EMC	FCC Class "A", VCCI, C-tick, CE, KCC (TBD)
	ErP / Energy Star	Yes / Yes (Energy Star 5.1) (TBD)
MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	No
	External Media player Attachable	MP700, MP500 (PC Built-in Ready)
SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-w 1.3 / Elite-w lite 1.3 / Elite-c 1.3
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual, ESG
	Optional	Wall Mount, Speaker, Option Board (Box type)

※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

DIMENSION (unit : mm)

