

Media Player Integrated Solution

LCD WIDESCREEN FULL HD DISPLAY VS20

VS20 42" 47" 55"



MEDIA PLAYER INTEGRATED SOLUTION

The solution integrated with media player allows you to cut down the extra cost for a media player.



USB MULTI-MEDIA PLAYBACK

USB multi-media playback is simple, easy solution without additional cost.

EASY & FAST DELIVERY OF CONTENTS

Easily edit content with the Web-based management software, SuperSign Elite-w lite. SuperSign Elite-w lite is provided with free templates, which allows easy and fast contents delivery.



VS20 Series



USB Memory
(USB Multi-media playback)



Free Software
(SuperSign Elite-w lite)



SuperSign Elite-w lite




Free Templates

IPS SUPERB PICTURE QUALITY

NO BLACKENING DEFECT

Hardly affected by light or heat, hence no blackening.




IPS

Normal

TRUE WIDE

No color changes or distortion from any viewing angle.



IPS

Normal

STABLE PANEL

When touch the screen, it can also display consistently with leaving no mark.



IPS

Normal

LCD WIDESCREEN FULL HD DISPLAY

VS20 42F", 47F", 55F"

VS20 42F", 47F", 55F"



FEATURES

- Media Player Integrated Solution
 - USB Multi-media Playback
- Easy & Fast Contents Delivery
 - SuperSign Elite-w lite bundled
- High Brightness (700nit)
- Narrow Uni Bezel Size
 - 42F" : 16.9mm, 47F" : 17.9mm, 55F" : 18.9mm
- Super IPS & Exclusive PD Panel
- Smart Energy Saving

SPECIFICATIONS

PANEL	Screen Size	42F", 47F", 55F"
	Panel Technology	IPS
	Aspect Ratio	16 : 9
	Native Resolution	1,920 x 1,080 (FHD)
	Brightness	700nit
	Contrast Ratio	42"/47" : 1,200:1, 55" : 1,300:1
	Dynamic CR	3,000:1
	Viewing Angle(H x V)	178 x 178
	Response Time	8ms (G to G, *WOT)
	CONNECTIVITY	Input (Rear)
Digital		HDMI(1), DVI(1), Display Port(1) with HDCP for all input
Analog		Component(1), AV(1), RGB(1) (Shared with D-Sub)
Audio		PC/AV/Component Audio In(1)
External Control		RS232C(1), RJ45(1)
USB		USB(1)
Output (Rear)		
Digital		DVI-D(1)
Analog		Component(1), Composite(1), RGB(1) (Shared with D-Sub)
Audio		External speaker
External Control	RS232C(1)	
PHYSICAL SPECIFICATION	Bezel Width	42" : 16.9mm 47" : 17.9mm 55" : 18.9mm
	Monitor Dimension(W x H x D)	42" : 96.7cm x 56.1cm x 12.5cm 47" : 107.95cm x 62.46cm x 12.29cm 55" : 125.1cm x 72.2cm x 10.4cm
	Weight(head)	42" : 17.5kg, 47" : 22.2kg, 55" : 34.5kg
	Carton Dimensions(W x H x D)	42" : 104.5cm x 66.0cm x 25.0cm 47" : 118.2cm x 74.3cm x 26.9cm 55" : 135.6cm x 85.8cm x 27.6cm
	Packed Weight	42" : 21.87kg, 47" : 29.6kg, 55" : 43.4kg

	VESATM Standard Mount	42" : 600mm x 400mm 47" / 55" : 800mm x 400mm
SPECIAL FEATURES	Additional	Smart Energy Saving, Multi-media playback, PIP/PIB, Temp Sensor, Tile mode (Up to 15x15), ISM Method, Key Lock
ENVIRONMENT CONDITIONS	Operation Temperature	0°C ~ 40°C
	Operation Humidity	10% ~ 80%
POWER	Power Supply	100-240V~, 50/60Hz
	Power Consumption	
	Typical / Smart Energy saving	42" : 170W(Typ) / 130W(Smart Energy Saving on) 47" : 180W(Typ) / 130W(Smart Energy Saving on) 55" : 260W(Typ) / 160W(Smart Energy Saving on)
	DPMS / Power Off	1.0W(Set only) 0.5W
STANDARD(CERTIFICATION)	Safety	UL / cUL / CB scheme / TUV
	EMC	FCC Class "B" / CE / KCC
	ErP / Energy Star	Yes / Yes (EPA 5.1)
MEDIA PLAYER COMPATIBILITY	Slot PC compatible (optional)	No
	External Media player Attachable	Yes
SOFTWARE COMPATIBILITY	Supersign Compatibility	Elite-w / Elite-w lite
ACCESSORY	Included	Remote Controller, Power Cable, RGB Cable, Manual
	Optional	42" : AP-WX60 SPO000K (Speaker), ST0000K (Stand) 47"/ 55" : AP-WX60 ST1000K (Stand), SPO000K (Speaker)

* WOT : Within Operation Temperature
 ※ Image may differ slightly from actual product. Specifications are subject to change without prior notice.

INTERFACE



DIMENSION (unit : mm)

